


HSF

NOTES:
 Current Rating: 1AMP
 Contact Resistance: 20mΩ max
 Withstand Voltage: 500V AC/DC
 Insulation Resistance: 1000MΩ min
 Operation Temperature: -40℃ to +105℃

Contact Material: Brass
 Contact plating: Au or Sn Over Ni
 Insulator Material: PA9T+33%GF(UL94V-0)

6 To 8 Pin No "D" Configuration

Recommended P.C.B Layout (Top Side)
 (PCB BOARD TOLERANCE ±0.05)



Ordering Information

3131-XX M XX B K 00 X 3

No. of Pins	Contact Plating	Color Insulator	Packing
10 34	G0=Gold Flash	B=Black	T=Tube
14 40	G3=10u"Gold		P=Tube+CAP
20 44	G4=15u"Gold		R=Tape&Reel+CAP
24 50	G5=30u"Gold		
26 60	S0=Gold Flash/Tin		
30 64	S3=10u"Gold/Tin		
32 80	S4=15u"Gold/Tin		
100	S5=30u"Gold/Tin		
	SN=Tin		

REV	DATE	MODIFICATION DESCRIPTION	CHANGE	OPERATION	DRAW	DATE	SCALE	FIT	PART NO.
A4	2016/11/11	Change Dimension	△△	OPERATION	DingWenMin	2016/11/11	SCALE	FIT	3131-XXMXXBK00X3
A3	2013/09/27	Modify		X.X ±0.40	CHECK	DATE	UNIT	mm	TITLE:
A2	2012/08/30	Modify CAP		X.XX ±0.25	APPROVE	DATE	SIZE	inch	1.27 BOX HEADER SMT
A0	2009/06/19	NEW		X.XXX ±0.15			SHEET	A4	H=5.70 WITH FORK
				Angle ± 3°			PROJ.	1/1	Customer NO.
				DIM TOL					

WCON

Http: www.wcon.com

WCON-Dongguan Tel: +86 769 85358920 Fax: +86 769 85358915 E-mail: sales@wcon.com
 WCON-Kunshan Tel: +86 512 57468408 Fax: +86 512 57468468 E-mail: salesks@wcon.com